

## Uddeholm Vanadis 60 SuperClean Stock Standard

**Flat bar**

 Soft annealed/Unmachined 

 Soft annealed/Rough machined 

mm	20	22	24	25	28	32	33	36	38	40	54	63	64	80	100	102	152
100				<input type="checkbox"/>													
108		<input type="checkbox"/>			<input type="checkbox"/>												
158					<input type="checkbox"/>												
202																	<input checked="" type="checkbox"/>
203	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>							
205													<input checked="" type="checkbox"/>				
210									<input type="checkbox"/>								
250														<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
260											<input type="checkbox"/>						
305							<input checked="" type="checkbox"/>										<input checked="" type="checkbox"/>
585												<input checked="" type="checkbox"/>					
600																	<input checked="" type="checkbox"/>
610																	<input checked="" type="checkbox"/>

**Round bar**

Soft annealed/Precision machined

Cold drawn fix length/Tolerance ISO ITh10

mm	10,3	12,3
	○	○

**Round bar**

Soft annealed/Rough machined

mm	16	18	20	22	26	32	38	42	52	65	90	102	130	160	210
	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●